GFM 226

Hidden Person Stowaway Detector

+44 (0)24 7630 3311

onice@gasaata.co.u

www.gasdata.co.uk

© Gas Data Limited
Unit 4, Fairfield Cour
Seven Stars Estate
Coventry, CV3 4LJ
United Kinadom

Our Mission

For nearly 30 years Gas Data have been designing and developing fully engineered gas analysis techniques. Our expertise is focused around generation of sustainable green energies, such as biogas. Every day, we help businesses all over

the world to deliver clean energy through our safe, reliable and scientific data analysis. We believe that the environment is our responsibility, which is why we are dedicated to empowering environmental evolution.

GFM Series Features

- Small portable design that is easy to hold in one hand
- High contrast LCD display
- User swapable battery pack
- Battery life ranging from 8 12 hours, depending on model
- Maximum charging time of 4 hours
- Charger suited to your country
- Protective weather proof leather case
- Supplied in a ready-to-go site kit
- Annual recalibration interval





Servicing

To ensure they are always reliable and operating at the best efficiency level, we strongly recommend our clients to perform an annual service and recalibration by either, Gas Data or any Gas Data approved service centre. Gas Data annual services for

the GFM series instruments come at a fixed price and include a 12 month warranty, so that our clients can be certain of their annual maintenance costs and enjoy the peace of mind. This cost includes a full service, calibration and repair of your instrument

at no additional cost throughout the life cycle of the product (the only exclusions are damages caused by negligence and mishandling of the instruments). Temporary courtesy hire instruments are available.



GFM 226



🖰 +44 (0)24 7630 3311 🔽 office@gasdata.co.uk 🌐 www.gasdata.co.uk





GFM 226 Technical Specification

| General | | | | |
|---------------------------|--------------------------------|--|--|--|
| Ambient Temperature Range | -10°c to 40°c | | | |
| Protection rating | IP65 | | | |
| Aspiration Rating | 300ml/min minimum | | | |
| Dimensions | 200mm x 100mm x 60mm (approx.) | | | |
| Typical Response Time | 30 seconds | | | |

Gas Measurements

| Channel | Sensor Type | Range | Resolution | Typical Accuracy |
|----------------|-------------|---------------|------------|------------------|
| Carbon Dioxide | IR | 0 - 10,000ppm | 1ppm | ± 100ppm |
| Oxygen | ECH | 0 - 25% | 0.1% | ± 0.2% |

GFM 226 Specific Features

- Ambient CO₂ level compensation
- Optional O₂ sensor
- Available Sensor accessories:
 - Straight needle probe
 - Under door probe
 - 1m lance probe

As well as carrying out visual searches of freight and vehicles, our officers use carbon dioxide probes, heartbeat detectors and sniffer dogs to detect the presence of people hiding in lorries.

> Brian Hill - UK Border Agency assistant director at Harwich Reported by BBC News

Customising gas and pressure combinations are not available on this model. The GFM 226 is a fixed configuration. All GFMs are available to hire or purchase. Please contact our team for details.

Other products available











Gas Flow Monitoring

ATEX Rated Systems